



		NT-2000Y	NT-2000SY	NT-2500Y	NT-2500SY
Swing Over Bed		ø1,000 mm ø39.37" (ø700 mm ø27.56" interference with cover)			
Swing Over Carriage		ø870 mm ø34.25" (ø700 mm ø27.56" interference with cover)			
Max. Turning Diameter		ø350 mm ø13.78"			
X / Z-axis Travel		260 / 580 mm 10.24" / 22.83"		260 / 780 mm 10.24" / 30.71"	
Main Spindle	Max. Spindle Power	15 kW 20 HP		22 kW 30 HP	
	Spindle Nose	A2-6		A2-8	
	Hole Through (Spindle / draw bar(opt))	ø77 mm / ø52 mm (ø66 mm) ø3.03" / ø2.05" (ø2.6")		ø91 mm / ø75 mm (ø80 mm) ø3.58" / ø2.95" (ø3.15")	
	Spindle Speed	4,500 rpm		3,500 rpm	
Sub Spindle	Max. Spindle Power	-	7.5 kW 10.1 HP	-	7.5 kW 10.1 HP
	Spindle Nose	-	A2-5	-	A2-5
	Hole Through (Spindle / draw bar(opt))	-	ø43 / ø33 mm ø1.69" / ø1.30"	-	ø43 / ø33 mm ø1.69" / ø1.30"
	Spindle Speed	-	6,000 rpm	-	6,000 rpm
Tail Stock Quill Diameter		ø90 mm ø3.54"	-	ø90 mm ø3.54"	-
Tail Stock Quill Taper	Dead Center	MT-4, Fixed Type	-	MT-4, Fixed Type	-
	Live Center (opt.)	MT-3, Rotary Type	-	MT-3, Rotary Type	-
Turret Capacity		12T with BMT 65			
Machine Weight		6,400 kg 14,109 lb	6,500 kg 14,330 lb	7,350 kg 16,204 lb	7,450 kg 16,424 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.