



	TC-16A	TC-16LA	TC-16B	TC-16LB
Swing Over Bed	ø550mm 21.65"			
Swing Over Carriage	ø320mm 12.6"			
Max. Turning Diameter	ø260mm 10.24"			
X/Z-axis Travel	150/370mm 5.91"/14.57"	150/600mm 5.91"/23.62"	150/370mm 5.91"/14.57"	150/600mm 5.91"/23.62"
Max. Spindle Power	15kW 20HP			
Spindle Nose	A2-5		A2-6	
Hole Through <small>(Spindle/draw bar)</small>	ø62/ø52mm 2.44"/2.05"		ø77/ø66mm 3.03"/2.6"	
Spindle Speed	5,000rpm		4,500rpm	
Tail Stock Quill Taper	MT-4 (TC-16A/B: opt.)			
Tail Stock Quill Diameter	ø75mm 2.95" (TC-16A/B: opt.)			
Turret Capacity	12T		10T	
Machine Weight	3,400kg 7,496 lb	3,700kg 8,157 lb	3,400kg 7,496 lb	3,700kg 8,157 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.