



	TC-26 (10"/12")	TC-26L (10"/12")	TC-36W (12")	TC-36 (12")	TC-46/1000	TC-46/1650	TC-46/2300	TC-46/3200
Swing Over Bed	ø500 mm ø19.69"		ø690 mm ø27.17"		ø850 mm ø33.5"			
Swing Over Carriage	ø350 mm ø13.78"		ø510 mm ø20.08"		ø720 mm ø28.4"			
Max. Turning Diameter	ø470 mm ø18.5"		ø590 mm ø23.23"		ø750 mm ø29.5"			
X/Z-axis Travel	250 / 700 mm 9.84" / 27.56"	250 / 1,100mm 9.84" / 43.31"	310 / 700 mm 12.2" / 27.56"	310 / 1,250 mm 12.2" / 49.21"	405 / 1,000 mm 15.94" / 39.4"	405 / 1,650 mm 15.94" / 65"	405 / 2,300 mm 15.94" / 90.6"	405 / 3,200 mm 15.94" / 126"
Max. Spindle Power	15 kW 20 HP		26 kW 35 HP		37 kW 49.6 HP			
Spindle Nose (opt.)	A2-8				A2-11 (A2-15, Big Bore)			
Hole Through (opt.) (Spindle/draw bar)	ø88 / ø78mm ø3.46" / ø3.07"		ø105 / ø93 mm ø4.13" / ø3.66"		ø130 / ø117 mm (ø182 / ø165 mm) ø5.1" / ø4.6" (ø7.2" / ø6.5")			
Spindle Speed (opt.)	10"- 4,000 rpm (12"- 2,500 rpm)		2,500 rpm		2,000 rpm (1,200 rpm)			
Tail Stock Quill Taper (opt.)	MT-5, Fixed Type (MT-4, Rotary Type)		MT-4, Rotary Type		MT-5, Fixed Type (MT-5, Rotary Type)			
Turret Capacity (opt.)	12T (8T)				10T			
Machine Weight	4,400 kg 9,700 lb	5,500 kg 12,125 lb	5,450 kg 12,015 lb	7,000 kg 15,432 lb	12,500 kg 27,558 lb	13,500 kg 29,762 lb	14,300 kg 31,526 lb	15,500 kg 34,171 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.  
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.